



**BUREAU
VERITAS**



EXCELLENCE IN QUALITY



**Long Lasting, Flexible & Strongest
ISO Certified**

18th Floor (B Wing),
Golden Jubilee Towers,
Ohio Street, Dar-Es-Salaam
www.lodhiaindustries.com



Dar-es-Salaam:

+255 22 211 3258

+255 22 211 3259

sm.marketing@lodhiagroup.com

Arusha:

+255 27 254 8504

+255 27 254 8520

TRITANK TECHNICAL SPECIFICATION

PRODUCT: Water Storage Tank, BRAND: Lodhia Tritank, GUIDELINES : TZS 892-1: 2019

PHYSICAL PROPERTIES

SIZE	500 LTR	1000 LTR	1500 LTR	2000 LTR	3000 LTR	5000 LTR	7000 LTR	7500 LTR	10000 LTR
ACTUAL DIAMETER (mm)	850	1070	1280	1380	1580	1870	2070	2260	2340
ACTUAL HEIGHT (mm)	1030	1300	1445	1610	1800	2070	2300	2745	2590

DOUBLE LAYERED: Colored Outside and White Inside (for hygiene)

SURFACE FINISH: Smooth Internal & External Surfaces

AVAILABLE COLORS: Black, Blue, Green & White

MECHANICAL PROPERTIES

TENSILE STRENGTH: 17 MPA

BASE MATERIAL

100% Virgin Linear Low Density Poly Ethylene

HANDLING & INSTALLATION

Handling & installation should be referred from Lodhia Tritank Installation Guide booklet.

FOOD CONTACT REGULATION

Tritank is suitable for food contact. Detailed information of raw material from the supplier can be provided on request.

